

Test Report Date: Nov.24, 2023 Page 1 of 5

IQ-BOX GmbH & Co. KG

Rudolf-Diesel-Str. 9, 90513, Zirndorf, Germany

Sample Description: TEX-LUX DIAMOND/200gsm

Model No: IQTLD-TF-320100.1123
Origin of the Product(s): CHINA

Destination of the Product(s): EUROPE

Main Substance: POLYESTER

The above data and information was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion.

SGS Ref No.:

Sample Receiving Date: Nov.09, 2023

Test Performing Date: Nov.09, 2023 to Nov.24, 2023

Test Requested:

EN 13501-1:2018 Fire classification of construction products and building elements – Part 1: Classification using data from reaction to fire tests.

Test Results: -- See attached sheet --

Signed for and on behalf of Shunde Branch SGS-CSTC Co., Ltd.

Irvette Zhang Approved signatory





Test Report Date: Nov.24, 2023 Page 2 of 5

I. Test conducted

This test is conducted as per EN 13501-1:2018 Fire classification of construction products and building elements – Part 1: Classification using data from reaction to fire tests. And the test methods as following:

- 1. EN 13823:2020+A1:2022 Reaction to fire tests for building products Building products excluding floorings exposed to the thermal attack by a single burning item.
- EN ISO 11925-2:2020 Reaction to fire tests Ignitability of products subjected to direct impingement of flame — Part 2: Single-flame source test.

II. Details of classified product

Sample Description	Fabric
Color	White
Thickness	0.25mm
Area density	201g/m ²

Mounting and fixing:

Test substrate was calcium silicate board meets the requirement of EN13501-1,of Class A2-s1,d0, the density of 900 kg/m³ and thickness of 10mm.

Specimen was installed on the substrate by screw. There was no joint between specimens. Specimen had a distance of at least 80mm from the backing board.

III. Test results

Test methods	Parameter	Number of tests	Results
EN 13823	FIGRA _{0.2MJ} (W/s)		0.0
	FIGRA _{0.4MJ} (W/s)		0.0
	Whether lateral flame spread (LFS) to the edge of specimen (Yes/No)		No
	THR _{600s} (MJ)	3	0.5
	SMOGRA (m²/s²)		0.5
	TSP _{600s} (m ²)		14.2
	Flaming particles or droplets (Yes/No)		No
EN ISO 11925-2 Exposure = 30 s	Fs≤150mm within 60 s (Yes/No)	12	Yes
	Ignition of the filter paper (Yes/No)	12	No

Note:

FIGRA_{0.2MJ} - Fire growth rate index at THR threshold of 0,2 MJ [W/s]

FIGRA_{0.4MJ} - Fire growth rate index at THR threshold of 0,4 MJ [W/s]





Test Report Date: Nov.24, 2023 Page 3 of 5

THR_{600s} -Total heat release within 600 s [MJ]

SMOGRA - Smoke growth rate [m²/s²]

TSP_{600s}- Total smoke production within 600 s [m²]

IV. Classification and field of application

a) Reference of classification

This classification has been carried out in accordance with EN 13501-1:2018.

b) Classification

The product, TEX-LUX DIAMOND/200gsm (as described by the sponsor), in relation to its reaction to fire behaviour is classified:

Fire behaviour		Smoke production			Flaming droplets	
В	_	s	1	,	d	0

Reaction to fire classification: B - s1, d0

Remark: The classes with their corresponding fire performance are given in annex A.

c) Field of application

This classification is valid for the following product parameters:

--- Characteristics as described in section II of this test reports.

This classification is valid for the following end use applications:

- --- With all substrates classified as A1 or A2
- --- With mechanically fixing
- --- No joint

Limitations

This classification document does not represent type approval or certification of the product.

Warning:

The test laboratory has, therefore, played no part in sampling the product for the test, although it holds appropriate references, supplied by the manufacturer, to provide for traceability of the samples tested.





Test Report Date: Nov.24, 2023 Page 4 of 5

Statement:

This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.

Note: This document cannot be reproduced except full, without prior written approval of the Company.

Annex AClasses of reaction to fire performance for construction products excluding floorings and linear pipe thermal insulation products

Class	Test method(s)		Classification criteria	Additional classification	
	EN ISO 1182 ^a	and	△ <i>T</i> ≤30°C , and △ <i>m</i> ≤50%, and t _r =0(i.e. no sustained flaming)	-	
A1	EN ISO 1716		PCS≤2.0MJ/kg ^a and PCS≤2.0MJ/kg ^{bc} and PCS≤1.4MJ/m ² ^d and PCS≤2.0MJ/kg ^e	-	
	EN ISO 1182 ^a or		△ <i>T</i> ≤50°C , and △ <i>m</i> ≤50%, and t≤20 s	-	
A2	EN ISO 1716	and	PCS≤3.0MJ/kg a and PCS≤4.0MJ/m² b and PCS≤4.0MJ/m² d and PCS≤3.0MJ/kg e	-	
	EN 13823		FIGRA _{0.2MJ} ≤120W/s and LFS < edge of specimen and THR _{600s} ≤7.5MJ	Smoke production ^f and Flaming droplets/particles ^g	
В	EN 13823	and	FIGRA _{0.2MJ} ≤120W/s and LFS < edge of specimen and THR _{600s} ≤7.5MJ	Smoke production ^f and - Flaming droplets/particles ^g	
	EN ISO 11925-2 ¹ Exposure =30s		Fs≤150mm within 60s		
С	EN 13823	and	FIGRA _{0.4MJ} ≤250W/s and LFS < edge of specimen and THR _{600s} ≤15MJ	Smoke production ^f and Flaming droplets/particles ^g	
	EN ISO 11925-2 ¹ Exposure=30s		<i>F</i> s≤150mm within 60 s	Triaming droplets/particles	
	EN 13823	and	FIGRA _{0.4MJ} ≤750W/s	Smoke production ^f and	
D	EN ISO 11925-2 ¹ Exposure=30s		<i>F</i> s≤150mm within 60 s	Flaming droplets/particles ^g	
Е	EN ISO 11925-2 ⁱ Exposure =15s		<i>F</i> s≤150mm within 20 s	flaming droplets/particles h	
F	EN ISO 11925-2 Exposure = 15 s		Fs > 150mm within 20 s		





Test Report Date: Nov.24, 2023 Page 5 of 5

^aFor homogeneous products and substantial components of non-homogeneous products.

^bFor any external non-substantial component of non-homogeneous products.

^cAlternatively, any external non-substantial component having a PCS ≤ 2,0 MJ/m², provided that the product satisfies the following criteria of EN 13823: FIGRA ≤ 20 W/s, and LFS < edge of specimen, and THR_{600s} ≤ 4,0 MJ, and s1, and d0.

^dFor any internal non-substantial component of non-homogeneous products.

^eFor the product as a whole.

 f s1 = SMOGRA ≤ 30m²/s² and TSP $_{600s}$ ≤ 50m²; s2 = SMOGRA ≤ 180m²/s² and TSP $_{600s}$ ≤ 200m²; s3 = not s1 or s2

gd0 = No flaming droplets/ particles in EN 13823 within 600 s;

d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s;

d2 = not d0 or d1.

Ignition of the paper in EN ISO 11925-2 results in a d2 classification.

^h Pass = no ignition of the paper (no classification);

Fail = ignition of the paper (d2 classification).

i Under conditions of surface flame attack and, if appropriate to the end–use application of the product, edge flame attack.

Photo Appendix:



SGS authenticate the photo on original report only

End of Report

